
RF292AJB Datasheet

Product Name // 2.92mm Straight Jack RF Connector

🗱 View Product Page

bulgin



// Product Description:

- O 2.92mm Straight Jack RF Connector
- O Maximum Voltage: 250V
- O Temperature range: -65°C to +165°C
- O Frecuency range: 0GHz 40GHz
- O VSWR:

- O Dielectric withstanding Voltage: >750V
- O Impedance: 500hm
- O Body Material: Stainless Steel Passivation
- O Contact Material: Beryllium Copper

// General Information:

Product Display Title:
Product Family:
Product Series:
Body Length:
Body Material:
Centre Contact Retention Force:
Contact Pin Material:
Min Coupling Torque:
Max Coupling Torque:
Dielectric Withstanding Voltage:
Durability:
Function:
Impedance:
Insulation Resistance:
Insulator:
Max Operating Temperature:
Min Operating Temperature:
Min Operating Frequency:
Max Operating Frequency:
Socket Diameter:
Thread Size:
Voltage Max:
Vswr:

2.92mm Series Straight Connector Radio Frequency Connectors 2.92mm Series 10.80mm Stainless Steel Passivation >20N Beryllium Copper 0.80Nm 1.10Nm >750V >500 cycles Female to Female RF Connector 50Ohm >5000MOhm UNFILLED ULTEM 1000/PEI +165°C -65°C 0GHz 40GHz 0.30mm 1/4 36UNS 2A 250V <1.30

// Product PDF Links

2.92mm Series Product Datasheet

// Product 3D CAD Model Links

RF292AJB3D CAD Model