


RF292APG Datasheet

Product Name // 2.92 Straight Plug for STA 142, UFB142A, GORE 3507, 1401 Cable

 [View Product Page](#)



// Product Description:

- | | |
|---|---|
| <ul style="list-style-type: none"> ⊕ 2.92 Straight Plug for STA 142, UFB142A, GORE 3507, 1401 Cable ⊕ Maximum Voltage: 250V ⊕ Temperature range: -40°C to +85°C ⊕ Frequency range: 0GHz - 40GHz ⊕ VSWR: <1.25 | <ul style="list-style-type: none"> ⊕ Dielectric withstanding Voltage: >750V ⊕ Impedance: 50Ohm ⊕ Body Material: Stainless Steel Passivation ⊕ Contact Material: Beryllium Copper |
|---|---|

// General Information:

Product Display Title:	2.92mm Series Straight Connector
Product Family:	Radio Frequency Connectors
Product Series:	2.92mm Series
Body Length:	26.90mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>20N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>750V
Durability:	>500 cycles
Function:	Male RF Connector
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	UNFILLED ULTEM 1000/PEI
Max Operating Temperature:	+85°C
Min Operating Temperature:	-40°C
Min Operating Frequency:	0GHz
Max Operating Frequency:	40GHz
Thread Size:	1/4 36UNS 2A
Voltage Max:	250V
Vswr:	<1.25

// Product PDF Links

 [2.92mm Series Product Datasheet](#)

// Product 3D CAD Model Links

 [RF292APG3D CAD Model](#)