
RFAA185P185P Datasheet

Product Name // 1.85mm Plug to Plug RF Adapter

View Product Page

* Representative product image only





// Product Description:

- 1.85mm Plug to Plug RF Adapter
- Maximum Voltage: 150V
- Temperature range: -40°C to +85°C
- Frecuency range: 0GHz - 65GHz
- VSWR: <1.25
- Dielectric withstanding Voltage: >500V
- Impedance: 50Ohm
- Body Material: Stainless Steel Passivation
- Contact Material: Beryllium Copper

// General Information:

Product Display Title:	RF Adapter Series 1.85mm Straight
Product Family:	Radio Frequency Connectors
Product Series:	RF Adapter Series
Body Length:	20.70mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>20N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>500V
Durability:	>500 cycles
Function:	Male to Male RF Adapter
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	ULTEM 1000/PEI
Max Operating Temperature:	+85°C
Min Operating Temperature:	-40°C
Min Operating Frequency:	0GHz
Max Operating Frequency:	65GHz
Voltage Max:	150V
Vswr:	<1.25

// Product PDF Links

RF Adapter Series Product...

// Product 3D CAD Model Links

RFAA185P185P3D CAD Model