RFAA240P240J Datasheet




Product Name // 2.4mm Plug to Jack RF Adapter

View Product Page

* Representative product image only





// Product Description:

- 2.4mm Plug to Jack RF Adapter
- Maximum Voltage: 150V
- C Temperature range: -40°C to +85°C
- Frecuency range: 0GHz 50GHz
- O VSWR:

- O Dielectric withstanding Voltage: >500V
- O Impedance: 500hm
- O Body Material: Stainless Steel Passivation
- O Contact Material: Beryllium Copper

// General Information:

Product Display Title:

Product Family:

Product Series: Body Length:

Pody Motorial

Body Material:

Centre Contact Retention Force:

Contact Pin Material: Min Coupling Torque: Max Coupling Torque:

Dielectric Withstanding Voltage:

Durability: Function: Impedance:

Insulation Resistance:

Insulator:

Max Operating Temperature: Min Operating Temperature: Min Operating Frequency: Max Operating Frequency:

Thread Size: Voltage Max: Vswr: RF Adapter Series 2.40mm Straight

Radio Frequency Connectors

RF Adapter Series

18.60mm

Stainless Steel Passivation

>20N

Beryllium Copper

0.80Nm 1.10Nm >500V

>500 cycles

Male to Female RF Adapter

500hm >5000MOhm ULTEM 1000/PEI

+85°C -40°C 0GHz 50GHz M7x0.75 6g 150V <1.20

// Product PDF Links



// Product 3D CAD Model Links



RFAA240P240J3D CAD Model