


Product Name // 2.92mm Plug to Plug RF Adapter
 [View Product Page](#)

* Representative product image only


// Product Description:

- ⊞ 2.92mm Plug to Plug RF Adapter
- ⊞ Maximum Voltage: 250V
- ⊞ Temperature range: -40°C to +85°C
- ⊞ Frequency range: 0GHz - 40GHz
- ⊞ VSWR: <1.20
- ⊞ Dielectric withstanding Voltage: >750V
- ⊞ Impedance: 50Ohm
- ⊞ Body Material: Stainless Steel Passivation
- ⊞ Contact Material: Beryllium Copper

// General Information:

Product Display Title:	RF Adapter Series 2.92mm Straight
Product Family:	Radio Frequency Connectors
Product Series:	RF Adapter Series
Body Length:	21.60mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>20N
Contact Pin Material:	Beryllium Copper
Dielectric Withstanding Voltage:	>750V
Durability:	>500 cycles
Function:	Male to Male RF Adapter
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	ULTEM 1000/PEI
Max Operating Temperature:	+85°C
Min Operating Temperature:	-40°C
Min Operating Frequency:	0GHz
Max Operating Frequency:	40GHz
Voltage Max:	250V
Vswr:	<1.20

// Product PDF Links
 [RF Adapter Series Product...](#)
// Product 3D CAD Model Links
 [RFAA292P292P3D CAD Model](#)