


**Product Name // N Jack Straight RF Connector, Bulkhead**
[View Product Page](#)

**// Product Description:**

- ⊞ N Jack Straight RF Connector, Bulkhead
- ⊞ Maximum Voltage: 500V
- ⊞ Temperature range: -55°C to +155°C
- ⊞ Frequency range: 0GHz - 18GHz
- ⊞ VSWR: <1.30
- ⊞ Dielectric withstanding Voltage: >1500V
- ⊞ Impedance: 50Ohm
- ⊞ Body Material: Stainless Steel Passivation
- ⊞ Contact Material: Beryllium Copper

**// General Information:**

Product Display Title:	N Type Series Bulkhead
Product Family:	Radio Frequency Connectors
Product Series:	N Type Series
Body Length:	20.6mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>26.7N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>1500V
Durability:	>500 cycles
Function:	Female RF Bulkhead
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	Adapter ASTM D 1710 & PEI
Max Operating Temperature:	+155°C
Min Operating Temperature:	-55°C
Min Operating Frequency:	0GHz
Max Operating Frequency:	18GHz
Pin Diameter:	2.70mm
Pin Length:	5.00mm
Thread Size:	5/8 24UNEF 2A
Voltage Max:	500V
Vswr:	<1.30

**// Product PDF Links**
[N Type Series Product Datasheet](#)
**// Product 3D CAD Model Links**
[RFNAJNH3D CAD Model](#)