


Product Name // N Jack Straight RF Connector, Bulkhead
[View Product Page](#)

// Product Description:

- ⊗ N Jack Straight RF Connector, Bulkhead
- ⊗ Maximum Voltage: 500V
- ⊗ Temperature range: -55°C to +155°C
- ⊗ Frequency range: 0GHz - 18GHz
- ⊗ VSWR:
- ⊗ Dielectric withstanding Voltage: >1500V
- ⊗ Impedance: 50Ohm
- ⊗ Body Material: Stainless Steel Passivation
- ⊗ Contact Material: Beryllium Copper

// General Information:

Product Display Title:	N Type Series Bulkhead
Product Family:	Radio Frequency Connectors
Product Series:	N Type Series
Body Length:	20.6mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>26.7N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>1500V
Durability:	>500 cycles
Function:	Female RF Bulkhead
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	Adapter ASTM D 1710 & PEI
Max Operating Temperature:	+155°C
Min Operating Temperature:	-55°C
Min Operating Frequency:	0GHz
Max Operating Frequency:	18GHz
Pin Diameter:	2.70mm
Pin Length:	5.00mm
Thread Size:	5/8 24UNEF 2A
Voltage Max:	500V
Vswr:	<1.30

// Product PDF Links
[N Type Series Product Datasheet](#)
// Product 3D CAD Model Links
[RFNAJNH3D CAD Model](#)