RFSMAA4PAABFGB Datasheet




Product Name // SMA Straight Plug 4 Hole Flange RF Connector

View Product Page

* Representative product image only





// Product Description:

- 0 SMA Straight Plug 4 Hole Flange RF Connector
- 0 Maximum Voltage: 335V
- 0 Temperature range: -65°C to +165°C
- 0 Frecuency range: 0GHz - 26.5GHz
- 0 VSWR: <1.30

- Dielectric withstanding Voltage: >750V
- 0 Impedance: 500hm
- 0 Body Material: Stainless Steel Passivation
- 0 Contact Material: Beryllium Copper

// General Information:

Product Display Title:

Product Family:

Product Series:

Body Length: Body Material:

Centre Contact Retention Force:

Contact Pin Material:

Min Coupling Torque:

Max Coupling Torque: **Coupling Nut Retention Force:**

Dielectric Withstanding Voltage:

Durability:

Flange Mount Length:

Function: Impedance:

Insulation Resistance:

Insulator:

Max Operating Temperature:

Max Operating Frequency:

Pin Diameter: Pin Length:

Ptfe Length:

Min Operating Temperature:

Mount Hole Distance:

Min Operating Frequency:

Ptfe Diameter:

Voltage Max:

Vswr:

SMA Series Pin with Extended PTFE 4 Hole Flange

Radio Frequency Connectors

SMA Series 12.70mm

Stainless Steel Passivation

>26.7N

Beryllium Copper

0.80Nm

1.10Nm

>27.2Kg >750V

>500 cycles

9.50mm

Male Flange Mount RF Connector

500hm

>5000MOhm

Adapter ASTM D 1710

+165°C

-65°C

6.35mm

0GHz

26.5GHz

0.38mm

2.00mm

4.00mm

3.00mm 335V

<1.30

// Product PDF Links



SMA Series Product Datasheet

// Product 3D CAD Model Links



RFSMAA4PAABFGB3D CAD Model