
RFTERM292P05W Datasheet



Product Name // 2.92mm Plug Termination (0.5W)

View Product Page





// Product Description:

- 2.92mm Plug Termination (0.5W)
- Maximum Voltage: 335V
- O Temperature range: -65°C to +165°C
- Frecuency range: 0GHz 40GHz
- O VSWR:

- O Dielectric withstanding Voltage: >750V
- O Impedance: 500hm
- O Body Material: Stainless Steel Passivation
- O Contact Material: Beryllium Copper

// General Information:

Product Display Title:

Product Family:

Product Series:

Average Power:

Body Length:

Body Material:

Centre Contact Retention Force:

Contact Pin Material:

Dielectric Withstanding Voltage:

Durability: Function:

Impedance:

Insulation Resistance:

Insulator:

Max Operating Temperature: Min Operating Temperature:

Min Operating Frequency: Max Operating Frequency:

Voltage Max:

Vswr:

RF Termination Series 2.92mm

Radio Frequency Connectors

RF Termination Series

<0.5W

12.80mm

Stainless Steel Passivation

>26.7N

Beryllium Copper

>750V

>500 cycles

Male RF Termination

50Ohm

>5000MOhm

UNFILLED ULTEM 1000/PEI

+165°C

-65°C 0GHz

40GHz

335V

<1.20

// Product PDF Links



RF Termination Series Product..

// Product 3D CAD Model Links



RFTERM292P05W3D CAD Model