


SLLP3002M5 Datasheet

Product Name // Photoelectric sensor SLLP3002M5

 [View Product Page](#)



// Product Description:

- Light Source=Red LED
 - Sensing Distance=2 - 30mm
 - Sensing Method=Reflective, Diffuse
 - Voltage - Supply=12 - 24 VDC
 - Response Time=<0.5 ms
 - Ingress Protection=IP67
 - Body Material=SUS 316L
- Connection Method=M5
 - Cable Length=2M
 - Operating Temperature=-10 +50 °C
 - Operating Humidity=35% - 85%(No condensation)
 - Vibration Resistance=10-50Hz double amplitudes, X. Y. Z. each direction 2 hours
 - Shock Resistance=1000m/s², X.Y.Z each direction 6 times

// General Information:

Product Display Title:	Photoelectric Sensor
Product Family:	Sensors
Product Series:	Photoelectric Sensors
Body Material:	SS 316L
Cable Length:	2m
Connection Method:	M5
Ip Rating:	IP67
Light Source:	Red LED
Max Operating Temperature:	+50°C
Min Operating Temperature:	-10°C
Operating Humidity:	35% - 85%(No condensation)
Operation Mode:	Light on
Output Configuration:	NPN
Response Time:	<0.5 ms
Sensing Distance:	2 - 30mm
Sensing Method:	Reflective, Diffuse
Shock Resistance:	1000m/s², X.Y.Z each direction 6 times
Vibration Resistance:	10-50Hz double amplitudes?X. Y. Z. each direction 2 hours
Voltage Supply:	12V - 24V

// Product PDF Links



// Product 3D CAD Model Links

