

# 1500 Twin Units Switches and Indicators

16A 250Vac



## Key Features

- Twin unit rocker switch
- Choice of switching circuits including 3 position
- Push-on, solder and PCB terminals
- Choice of bezel styles
- Choice of panel cut outs
- Matching indicator
- Single Contact switches
- Splash resistant option
- Panel cut out 'A' style: 27.2 x 22.3mm

## Approvals and Specifications

16(4)A 250Vac T125


UL CSA 16A 250Vac  
UL CSA (2 posn) 250Vac 1hp, 125Vac  
1/2hp, (3 posn) 250 Vac  
1/2hp, 125Vac 1/4hp  
UL 85°C, file E45221, CSA file LR10990

For versions with High Inrush or for 50,000 operations,  
3mm contact gap except where marked  $\mu$ .

Terminal	Function	Rocker	Body	Finish	Body Colour	Rocker Colour
<b>C</b>  6.3 x 0.8	Approvals & ratings vary with function ON OFF Switches - ON when pressed over terminal 1 or 4 	<b>A</b> Softline (Matt only) 	Panel Cut - outs      Bezel <b>A</b>  22.3/22.4      27.2/27.3      30.2/25.0 Gloss or Matt	<b>M</b> Matt	<b>B</b> Black	Un-Lit  <b>B</b> Black
<b>H</b>  4.8 x 0.8	<b>1500</b>  ON - OFF	<b>B</b> Softline (Matt only) 	<b>B</b>  22.1/22.2      30.0/30.1      33.4/25.0 Matt only	<b>G</b> Gloss	<b>W</b> White	<b>R</b> Red
<b>T</b>  Solder	<b>1510 <math>\mu</math></b>  ON - ON	<b>W</b> Softline (Matt only) 	<b>L</b>  22.1/22.2      30.0/30.1      32.0/25.0 Matt only	Applies to both Rocker & Body		<b>W</b> White
<b>K</b>  2.0 x 1.2	<b>1520 <math>\mu</math></b>  ON - OFF - ON	<b>X</b> Softline (Matt only) 	<b>Q</b>  22.3/22.4      28.2/28.3      30.2/25.0 Gloss or matt			Lit  <b>A</b> Amber
<b>X</b>  4.0 x 1.2	<b>0430</b>  Indicator	<b>A</b> Softline (Matt only) 	<b>R</b>  25.3/25.4      28.4/28.5      33.2/28.9 Matt only			<b>C</b> Clear
			<b>T</b>  22.3/22.4      28.2/28.3      30.2/25.0 Matt only			<b>G</b> Green
						<b>R</b> Red

## Dimensions


**Panel thickness**  
**A,Q** 0.75 to 3.3mm  
**L,B,T** 0.75 to 2.5mm  
**R** 0.75 to 3.0mm



Call sales for terminal spacing details


## Twin units

Two single switches or a switch and an indicator light can be assembled side by side in one double Contact body.



For twin units the first set of order format details refer to the left hand unit, when looking at the front of the assembly.  
 (This has terminal numbers 1, 2 & 3)

## Splash Resistant



Feather edge seals and a close fitting collar protect current carrying parts from moisture.

B option has Hytrel collar/seals for enhanced protection.

Insert Colour	Lamp Voltage	Legend	Legend Colour	Options
Blank	Blank	Blank	Blank	<a href="#">Finish</a> Matt is standard.
<b>R</b> Red	<b>2</b> 125V Neon	<b>602A</b>	<b>B</b> Black	<a href="#">Colour</a> Call factory for custom colours. A full range is available for large orders.
<b>W</b> White	<b>3</b> 250V Neon		<b>W</b> White	<a href="#">Legend printing</a> Select from the examples or call factory for custom legends.
	<b>5</b> 12Vdc LED (P Rocker)			<a href="#">Lamp voltage</a> Call factory for details.
	<b>6</b> 24Vdc LED (P Rocker)			
	<b>7</b> 12V Filament			
	<b>8</b> 24Vdc Filament			

## Examples



C1500A/C1500AL



C1500A/C0430AL



C1500X/C1500XL



C1520A/C1510AL



C1500A/C1520AL



C0430A/C0430AL