



## Certification Record

CUSTOMER	CLASS	FILE
Elektron Technology UK Limited Broers Building, JJ Thomson Avenue Cambridge CB3 0FA United Kingdom	<a href="#">6221-02</a> ATTACHMENT PLUGS-Fuseless	043989_0_000
	<b>Refer to Class Description for program details</b>	

- Motor attachment plugs, 15A, 250V, 2-pole, 3-wire grounding, Types P575, P580, P580/1, Q1950, P579, Q2112/5, P590, P595, P580/PC/7MM, P580/PC/7MM/LC, Q2422/1, Q2422/2.
- Motor attachment plugs (flanged equipment power inlets), 2-pole, 2-wire, Cat Nos. P690/PC, P690/PC/12132, P690/PC/7 and P690/PC/7/LC; 2-pole, 3-wire, Cat Nos. P580/PC/12132; 15A, 250V.
- Motor attachment plugs, 15A, 250V, 2-pole, 2-wire, Type P690, P691.
- Special purpose coupler, 10A, 250V, 2-pole, 3-wire grounding, Type P597.
- Special-use pull-off plug, 2-pole, 3-wire grounding, 10A, 250V, Type P587.
- Special purpose couplers, 2-pole, 2-wire, 15A, 250V Types P705, P725.
- Special purpose couplers, 2-pole, 2-wire, 10A, 250V, Types P715, P772, P782.
- Special purpose couplers, 2-pole, 3-wire grounding, 15A, 250V, Types P675, P695; 10A, 250V, Types P685, P686, P770, P780.

### TO THE REQUIREMENTS OF CSA STANDARD C22.2 NO. 182.3-M1987

- Special-use pull-off plug, 2-pole, 3-wire grounding, 10A, 250V, type P587/SE.
- Motor attachment plugs (appliance inlets), Type P.575/PC, 15A, 250V ac, Types BZM.1, BZM.2, 10A, 250V ac, 2-pole, 3-wire grounding, BZM.1A and BZM.2A, 2 pole, 2 wire (no ground); Types QX3171 and QX2936, 2 pole, 2 wire (no ground) with switch.
- Motor attachment plugs (appliance inlets), 2 pole, 3 wire grounding, Type P783 and P793, 15A, 250V ac.
- Motor attachment plugs (appliance inlets), types P784, P785 and P786, rated 2.5A, 250V, 2-pole, 2-wire, non-polarized.
- Rewireable appliance connectors, 2 pole, 3 wire grounding, Type P686 and P686/SE, 10A, 250V ac.

#### Notes:

1. The plugs are sold only to manufacturer's for assembly of Certified electrical equipment.
2. Each plug or coupler may have the following suffix added to the type designation, /PC, /TERM, /110, /187, /250 or /28, /48, /63 as appropriate.
3. Couplers may also be marked for panel thickness, 0.5-4.0mm.

- Special purpose coupler, Cat No P599, 20A, 250V, 2 pole, 3 wire grounding.

Note: The special purpose coupler is certified only as a component, for use with other certified

equipment where the suitability of the combinations are determined by the Canadian Standards Association.

pg

---

Copyright © 2012 CSA International. All rights reserved.